

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H04B 7/005</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/33478</b> (43) International Publication Date: <b>8 June 2000 (08.06.00)</b>
(21) International Application Number: <b>PCT/US99/28394</b> (22) International Filing Date: <b>30 November 1999 (30.11.99)</b> (30) Priority Data: 09/204,026      1 December 1998 (01.12.98)      US (71) Applicant: <b>QUALCOMM INCORPORATED [US/US]; 5775 Morehouse Drive, San Diego, CA 92121-1714 (US).</b> (72) Inventor: <b>SOLIMAN, Samir, S.; 11412 Cypress Canyon Park Drive, San Diego, CA 92131 (US).</b> (74) Agent: <b>GREENHAUS, Bruce, W.; Qualcomm Incorporated, 5775 Morehouse Drive, San Diego, CA 92121-1714 (US).</b>	(81) Designated States: <b>AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</b>  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: FORWARD AND REVERSE LINK POWER CONTROL USING POSITION AND MOBILITY INFORMATION

## (57) Abstract

A method and apparatus for dynamically adjusting a power control loop that attempts to maintain either the transmit power of a signal sent from a base station to a mobile station or the signal to noise ratio of a signal sent from the mobile station (300) to the base station (400) above a minimum threshold and below a maximum threshold. Location information that is representative of the distance and morphology between the mobile station (300) and the base station (400) and the velocity of the mobile station (300) are determined. The minimum and the maximum thresholds of the power control loop are then adjusted in accordance with the location and the mobility information such that the minimum and the maximum threshold vary as the distance and the morphology between the mobile station (300) and the base station (400) and the velocity of the mobile station (300) change. In addition, the step size used to increase or decrease the transmit signal power, is adjusted in accordance with the velocity of the mobile station (300). A transmitter sends the signal at a power level that is controlled by the power control loop with the adjusted minimum threshold.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

# FORWARD AND REVERSE LINK POWER CONTROL USING POSITION AND MOBILITY INFORMATION

## 5 BACKGROUND OF THE INVENTION

### I. Field of the Invention

10 The present invention relates generally to mobile radio communication systems. More particularly, the present invention relates to power control systems for controlling the power level of signals sent on the forward links of a mobile radio communication system, and for controlling the signal to noise ratios of signals sent on the reverse links of a mobile radio communication system. Even more particularly, the present  
15 invention relates to a novel system and method that dynamically adjusts the parameters of forward and reverse link power control loops based upon the position and velocity of a mobile station.

### II. Description of the Related Art

20 In mobile radio communication systems such as, for example, code division multiple access (CDMA) communication systems, the transmit power levels of signals sent between a base station and a mobile station are carefully controlled using power control loops. Typically, one power control  
25 loop is used to maintain the power level of signals on the forward link (i.e., signals sent from the base station to a mobile station) between a minimum and a maximum level. A different power control loop is similarly used to maintain the received signal to noise ratio of signals sent on the reverse link (i.e., the SNR measured at the base station of signals sent from a mobile  
30 station to the base station) between a minimum desired level and a maximum desired level. These power control loops typically adjust the transmit power of a signal upward or downward in fixed step wise increments (e.g., plus or minus 1 dB) in order to maintain either the power level or the signal to noise ratio of the signal between the minimum and  
35 maximum desired levels.

In early CDMA systems, forward link power control was typically accomplished using an open power control loop, whereas the reverse link power control system used a closed power control loop. Current CDMA systems use a closed power control loop for forward link power control and

it is expected that future CDMA systems will continue to use a closed power control loop for forward link power control.

Each geographic cell in a mobile radio communication system is typically serviced by a base station associated with the cell. In current systems, the parameters of the forward link power control loop (i.e., the minimum power level, maximum power level, and step size associated with the forward link power control loop) and the limits of the reverse link power control loop (i.e., the minimum desired signal to noise ratio, maximum desired signal to noise ratio, and step size associated with the reverse link power control loop) do not vary as the location and velocity of mobile units within the cell varies.

The transmit power requirements of signals sent between a base station and a mobile station vary as the mobile station moves within a cell. For example, as the mobile station moves closer to the base station, less transmit power is often required on the reverse link to achieve the same signal-to-noise ratio of the received signal at the base station. Thus, as the mobile station moves closer to the base station, the transmit power on the reverse link can often be reduced while maintaining the same signal-to-noise ratio of the received signal at the base station. In addition, less transmit power is also often required when the mobile station is stationary or moving slowly (as opposed to moving quickly) to achieve the same signal-to-noise ratio of the received signal at the base station. Thus, as the mobile station slows down, the transmit power on the reverse link can often be reduced while maintaining the same signal-to-noise ratio of the received signal at the base station.

The capacity of a given mobile radio communication system is limited by the transmit power available to the base station and the signal to noise ratio requirement on the reverse link. Thus, the capacity of the system could be increased if the base station transmit power and/or the signal to noise ratio on the reverse link in the system are reduced. In view of this, it would be desirable to have a power control system that could dynamically adjust the parameters of the forward and reverse link power control loops in response to the changing position and/or speed of a mobile station, so as to conserve transmit power and increase cell capacity.

## SUMMARY OF THE INVENTION

The present invention maximizes the capacity of a given cell by adjusting one or both limits of a power control loop based on the position of

a mobile station within the cell. In one embodiment, the present invention dynamically adjusts the parameters of a power control loop that attempts to maintain the transmit power of a signal sent from a base station to a mobile station above a minimum threshold. In this embodiment, location  
5 information that is representative of the distance and the morphology between the mobile station and the base station is determined. The minimum threshold of the power control loop is then adjusted in accordance with the location information such that the minimum threshold varies as the distance and the morphology between the mobile  
10 station and the base station change. A transmitter then transmits the signal at a power level that is controlled by the power control loop with the adjusted minimum threshold. This aspect of the invention can be used for controlling the minimum power level associated with the forward link power control loop.

15 In a further embodiment, the present invention dynamically adjusts the parameters of a power control loop that attempts to maintain the signal to noise ratio of a signal sent from the mobile station to the base station above a minimum threshold. In this embodiment, location information that is representative of the distance and the morphology between the  
20 mobile station and the base station is determined. The minimum threshold of the power control loop is then adjusted in accordance with the location and the morphology information such that the minimum threshold varies as the distance and the morphology between the mobile station and the base station change. A transmitter then transmits the signal at a power level that  
25 is controlled by the power control loop with the adjusted minimum threshold. This aspect of the invention can be used for controlling the minimum desired signal to noise ratio (i.e., the minimum desired signal to noise ratio of a reverse link signal received at the base station) in a reverse link power control loop.

30 In accordance with further alternative embodiments, the present invention also determines velocity information that is representative of the velocity of the mobile station. In these embodiments, the minimum threshold of a power control loop is adjusted based on the velocity information alone or, alternatively, the minimum threshold of the power  
35 control loop is adjusted based on both the velocity information and the current position of the mobile station. This aspect of the invention can also be used for controlling the minimum thresholds associated with both the forward and reverse link power control loops, and is especially useful in mixed wireless networks where there are both fixed position wireless users

(also referred to as wireless local loop users) and mobile wireless users (i.e., wireless users that change position.) In such mixed wireless networks, adjustment of the minimum thresholds associated with both the forward and reverse link power control loops based on the velocity of wireless user  
5 ensures efficient allocation of system resources.

In accordance with a still further aspect, the maximum threshold of a forward link power control loop (i.e., the power level below which the power control loop attempts to maintain the transmit power of the signal sent from the base station) is also adjusted in accordance with the location  
10 information (and optionally the velocity information) such that the maximum threshold varies as the distance and the morphology between the mobile station and the base station (and optionally the velocity of the mobile station) vary.

In accordance with yet a further aspect, the maximum threshold of a  
15 reverse link power control loop (i.e., the maximum desired signal to noise ratio below which the power control loop attempts to maintain the signal to noise ratio of a reverse link signal received at a base station) is also adjusted in accordance with the location information (and optionally the velocity information) such that the maximum threshold varies as the distance and  
20 the morphology between the mobile station and the base station (and optionally the velocity of the mobile station) vary.

In accordance with a still further aspect, the step size of a power control loop (i.e., the step wise power increment used in the power control loop to adjust the transmit power of the signal upward or downward) is also  
25 adjusted in accordance with the velocity information such that the step size varies as the velocity of the mobile station varies. In accordance with this aspect, the step size used by the power control loop is preferably reduced for stationary or slow moving mobile stations, and the step size is increased when a mobile station begins moving more quickly. This aspect of the  
30 invention can be used for controlling the step size of either a forward link or reverse link power control loop.

## BRIEF DESCRIPTION OF THE DRAWINGS

35 In order that the invention can be appreciated, a more particular description of the invention briefly described above will be rendered by reference to a specific embodiment thereof which is illustrated in the appended drawings. Understanding that these drawings depict only a typical embodiment of the invention and are not therefore to be considered

limiting of its scope, the invention and the presently understood best mode thereof will be described and explained with additional specificity and details through the use of the accompanying drawings in which:

Figure 1 is a flow diagram of a method for adjusting the minimum and maximum limits of the forward and reverse link power control loops in a mobile radio communication system, in accordance with a preferred embodiment of the present invention.

Figure 2 is a map showing a cell with several geographical regions each of which has a different minimum power threshold associated therewith for controlling the transmit power of reverse link signals transmitted from such regions to a base station, in accordance with a preferred embodiment of the present invention.

Figure 3 is a block diagram showing the components of an exemplary CDMA mobile station used to implement the power control systems of the present invention.

Figure 4 is a block diagram showing the components of an exemplary CDMA base station used to implement the power control systems of the present invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to Figure 1, there is shown a flow diagram of a method for adjusting the minimum limits, maximum limits, and step size increments of the forward and reverse link power control loops in a mobile radio communication system, in accordance with a preferred embodiment of the present invention. In step 110, a position  $P(x, y)$  of the mobile station is determined using, for example, measurements from both the Global Positioning Satellite (GPS) system and the system infrastructure. The position of the mobile station is preferably determined in this step using differential GPS and in accordance with the method disclosed in U.S. Patent Appl. No. 09/040,501, entitled "System and Method for Determining The Position of a Wireless CDMA Transceiver," filed March 17, 1998, which is owned by the assignee of the present invention, and the contents of which is incorporated herein in their entirety by reference. In an alternate embodiment, the position of the mobile station can be determined using at least three (and preferably more) terrestrial base stations in the system infrastructure.



In step 120, the motion of the mobile station is modeled (preferably using past positional measurements) in order to estimate the current velocity (or a range of potential velocities) of the mobile station. Map information, which places the mobile station on a street or highway, which is oriented in a known direction, may also be used to model the current velocity of the mobile station. Filtering methods can further enhance this trajectory estimation technique. A good example is to use a Kalman filter to adaptively track the mobile trajectory and hence predict its dynamic state in terms of speed and position.

In step 130, the position of the mobile station is applied to a look up table associated with a cell (such as Table I below) in order to determine the upper and lower limits of the forward and reverse link power control loops.

Position Information		Forward Link PC Loop Limits		Reverse Link PC Loop Limits	
<u>Longitude</u>	<u>Latitude</u>	<u>Power Ceiling</u>	<u>Power Floor</u>	<u>Desired SNR Maximum</u>	<u>Desired SNR Minimum</u>
$x_1$	$y_1$	$PMAX1_{FL}$	$PMIN1_{FL}$	$SNR\_MAX1_{RL}$	$SNR\_MIN1_{RL}$
$x_2$	$y_2$	$PMAX2_{FL}$	$PMIN2_{FL}$	$SNR\_MAX2_{RL}$	$SNR\_MIN2_{RL}$
$x_3$	$y_3$	$PMAX3_{FL}$	$PMIN3_{FL}$	$SNR\_MAX3_{RL}$	$SNR\_MIN3_{RL}$
$x_4$	$y_4$	$PMAX4_{FL}$	$PMIN4_{FL}$	$SNR\_MAX4_{RL}$	$SNR\_MIN4_{RL}$

TABLE I

In one embodiment, the power control loop values stored in the table are determined empirically by collecting data reflecting the power requirements of a mobile user as the user moves to different locations within a cell. For example, the data can be collected by giving a mobile

station with position location capability to a postman and monitoring the power requirements of the mobile station as the post man moves about the cell making postal deliveries. In this embodiment, the forward link power levels and the reverse link signal to noise ratio are monitored and stored at different locations in the cell as the mobile station moves about the cell. Thereafter, for each location or region in the cell being monitored, the  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values -- which represent the minimum and maximum desired signal to noise ratios associated with the reverse link power control loop to be applied at the location or region -- are selected by, for example, adding and subtracting predetermined margins from the reverse link signal to noise ratio of the reverse link signal that was measured at the base station when the mobile station was in the location or region. In other words, the  $SNR\_MAX_{RL}$  value for the region will be set by adding a predetermined margin of dB to the reverse link signal to noise ratio that was measured at the base station when the mobile station was in the location or region, and the  $SNR\_MIN_{RL}$  value for the region will be set by subtracting a predetermined margin of dB from the reverse link signal to noise ratio that was measured at the base station when the mobile station was in the location or region. Similarly, for each location or region in the cell being monitored, the  $PMAX_{FL}$  and  $PMIN_{FL}$  values -- which represent the power ceiling and floor of the forward link power control loop to be applied at the location or region -- are selected by, for example, adding and subtracting predetermined power margins from the measured forward link power level in the location or region. In other words, the  $PMAX_{FL}$  value for the region will be set by adding a predetermined margin of dB to the forward link power level that was measured when the mobile station was in the location or region, and the  $PMIN_{FL}$  value for the region will be set by subtracting a predetermined margin of dB from the forward link power level that was measured when the mobile station unit was in the location or region.

In step 130, after the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values are selected from the look up table, the values are adjusted based on the velocity of the mobile station. This aspect of the invention recognizes that low mobility users (e.g., mobile stations moving at less than 5 mph or pedestrian speed) will experience less fading than higher mobility users and that, as a result, the forward and reverse links associated with lower mobility users can operate within tighter power control limits. In accordance with this aspect of the invention, in cases where the user is moving below a predetermined speed such as 5 mph, a predetermined

amount (e.g., 2 dB) is subtracted from the  $PMAX_{FL}$  and  $SNR\_MAX_{RL}$  values and a predetermined amount (e.g., 2 dB) is added to the  $PMIN_{FL}$  and  $SNR\_MIN_{RL}$  values before the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values are applied to the power control loops in steps 140 and 150. This aspect of the invention similarly recognizes that high mobility users (e.g., mobile stations moving at more than 35 mph) will experience more fading than lower mobility users and that, as a result, the forward and reverse links associated with such higher mobility users should operate within wider power control limits. In accordance with this aspect of the invention, in cases where the user is moving above a predetermined speed such as, for example, 35 mph, a predetermined amount (e.g., 2 dB) is added to the  $PMAX_{FL}$  and  $SNR\_MAX_{RL}$  values and a predetermined amount (e.g., 2 dB) is subtracted from the  $PMIN_{FL}$  and  $SNR\_MIN_{RL}$  values before the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values are applied to the power control loops in steps 140 and 150.

Adjustment of the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  based on the velocity of the mobile station as is done in step 130 is especially important in mixed wireless networks where there are both fixed position wireless users (also referred to as wireless local loop users) and mobile wireless users (i.e., wireless users that change position.) In such mixed wireless networks, adjustment of the minimum thresholds associated with both the forward and reverse link power control loops based on the velocity of the wireless users ensures efficient allocation of system resources. For purposes of the present invention, the term "mobile station" shall refer to a mobile station such as mobile station 300 shown in Figure 3, regardless of whether the user of such station is a fixed position wireless user or a mobile wireless user.

In step 130, the velocity of the mobile station is also applied to a second look up table (such as Table II below) in order to determine the power adjustments step sizes to be used in the forward and reverse link power control loops:

Velocity Information	Forward Link PC Loop Step Size	Reverse Link PC Loop Step size
$0 < \text{Velocity} < v_1$	STEP1 <sub>FL</sub>	STEP1 <sub>RL</sub>
$v_1 < \text{Velocity} < v_2$	STEP2 <sub>FL</sub>	STEP2 <sub>RL</sub>
$v_2 < \text{Velocity}$	STEP3 <sub>FL</sub>	STEP3 <sub>RL</sub>

TABLE II

5 The values stored in Table II preferably reflect that a smaller step size will be required to adequately maintain the power or signal to noise ratio of a signal within predetermined limits in cases where the mobile station is moving more slowly. Where  $v_1$  and  $v_2$  are equal to 5 mph and 35 mph, respectively, exemplary values for STEP1<sub>RL</sub>, STEP2<sub>RL</sub> and STEP3<sub>RL</sub> are 0.25 dB, 10 0.5 dB and 1.0 dB, and exemplary values of for STEP1<sub>FL</sub>, STEP2<sub>FL</sub> and STEP3<sub>FL</sub> are  $\frac{1}{2}$ ,  $\frac{1}{3}$  and 1 times the normal power increment step size on the forward link power control loop. Use of this aspect of the invention reduces the power fluctuations on the forward and reverse links by keeping at a minimum, the size of each power adjustment made by the power control 15 loops.

Although in the embodiment described above, the power control loop parameters were adjusted in step 130 by predetermined amounts based on the velocity of the mobile station, it will be understood by those skilled in the art that the particular amounts used to adjust the power control loop 20 parameters represent a matter of design choice and that optimal values may be determined using empirical data for a given cell.

In steps 140 and 150, the PMA<sub>FL</sub>, PMIN<sub>FL</sub>, SNR\_MAX<sub>RL</sub> and SNR\_MIN<sub>RL</sub> values from the first look up table (which have been adjusted based on the mobility of the mobile station) are applied to the forward and reverse link power control loops and used as the upper and lower power limits of these control loops. Similarly, the STEP<sub>RL</sub> and STEP<sub>FL</sub> values from the second look up table are applied to the forward and reverse link power control loops and used as the step size used for power adjustment by these control loops. The process shown in Figure 1 is preferably repeated at 25

regular intervals so that the power control loops are regularly updated as a mobile station moves about a cell and/or its mobility varies.

Although in the preferred embodiment of the present invention, the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values from the look up table are adjusted based on the mobility (or velocity) of the mobile station before being applied to the forward and reverse link power control loops, in alternative embodiments the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values from the look up table may be applied to the forward and reverse link power control loops without any adjustment based on the mobility (or velocity) of the mobile station. In further alternate embodiments of the present invention, the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values may be adjusted based only on the mobility or velocity of the mobile station (and not the location of the mobile station within the cell) before being applied to the forward and reverse link power control loops by making the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values in the look up table location independent (i.e., in these embodiments the values in the table are set so that they do not vary based on position of the mobile station within the cell).

Referring now to Figure 2, there is shown a map of a cell 200 with several geographical regions (R0, R1, R2 and R3) each of which has different minimum and maximum thresholds associated therewith for controlling the transmit power of forward and reverse link signals transmitted from such regions to a base station. In this embodiment, the limits of the forward and reverse link power control loops vary in a stepwise manner based on regions within the cell. Thus, one set of  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values will be extracted from the look up table in step 130 whenever the mobile station is operating in region R0, a second set of  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $SNR\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values will be extracted from the look up table whenever the mobile station is operating in region R1, and so on. It will be understood by those skilled in the art that the  $PMAX_{FL}$ ,  $PMIN_{FL}$ ,  $PSN\_MAX_{RL}$  and  $SNR\_MIN_{RL}$  values could alternatively vary in a more continuous or less regular manner as a function of the distance of the mobile station from the center of the cell.

Referring now to Figure 3, there is a block diagram showing the components of an exemplary code division multiple access (CDMA) mobile station 300 used for implementing the power control systems of the present invention. The mobile station includes an antenna system 330, which is coupled through diplexer 332 to analog receiver 334 and transmit power amplifier 336. Antenna system 330 and diplexer 332 are of standard design

and permit simultaneous reception and transmission through one or more antennae. Antenna system 330 optionally includes one antenna for voice traffic, and a separate antenna for receiving GPS signals. Antenna system 330 collects signals transmitted to the mobile station from one or more base stations and the GPS system, and provides the signals through diplexer 332 to analog receiver 334. Receiver 334 is also provided with an analog to digital converter (not shown). Receiver 334 receives RF signals from diplexer 332, amplifies and frequency downconverts the signals, and provides a digitized output signal to digital data receivers 340, 342 and to search receiver 344. It will be understood that, although in the embodiment in Figure 3 only two digital data receivers are shown, a low performance mobile station might have only a single digital data receiver while higher performance units will have two or more digital data receivers to permit diversity reception. The outputs of receivers 340 and 342 are provided to diversity and combiner circuitry 348 which time adjusts the two streams of data received from the receivers 340 and 342, adds the streams together and decodes the result. Details concerning the operation of the digital data receivers 340, 342, the search receiver 344, and the diversity combiner and decoder circuitry 348 are described in U.S. Patent No. 5,101,501 entitled "Method and Apparatus for Providing A Soft Handoff In Communications In A CDMA Cellular Telephone System", which is assigned to the assignee of the present invention and incorporated herein by reference.

An output signal is provided from the decoder 348 to control processor 346. The output signal from the decoder will include, for example, any pilot signals from the base stations that will be used for making positional measurements, timing signals received from the GPS system, and other information such as modeling information and base station position information sent from a base station to the mobile unit. In response to this information, the control processor 346 determines the forward and/or reverse link power control parameters in accordance with the method shown in Figure 1 and the reverse link power control parameters are used with the power control unit in the mobile station to control the power level of the reverse link signals from the mobile station. All the steps shown in Figure 1 are preferably implemented in software on control processor 346; however, it will be understood by those skilled in the art that many of these steps could alternatively be implemented in the system infrastructure.

Referring now to Figure 4, there is shown a block diagram of the components of an exemplary CDMA base station 400 used for implementing the forward and reverse link power control systems of the present

invention. At the base station, two receiver systems are utilized with each having a separate antenna and analog receiver for diversity reception. In each of the receiver systems, the signals are processed identically until the signals undergo a diversity combination process. The elements within the  
5 dashed lines correspond to elements corresponding to the communications between the base station and one mobile station. Referring still to Figure 4, the first receiver system is comprised of antenna 460, analog receiver 462, searcher receiver 464 and digital data receivers 466 and 468. The second receiver system includes antenna 470, analog receiver 472, searcher receiver  
10 474 and digital data receiver 476. Cell-site control processor 478 is used for signal processing and control. Among other things, cell site processor 478 monitors the signals sent to and received from a mobile station in order to determine the position information used in the present invention, and this processor is also preferably used for performing the modeling of the mobile  
15 velocity in step 120. Cell site processor 478 optionally determines the forward and/or reverse link power control parameters in accordance with the method shown in Figure 1, and the forward link power control parameters are used with the power control unit in the base station to control the power level of the forward link signals from the base station.

Both receiver systems are coupled to diversity combiner and decoder circuitry 480. A digital link 482 is used to communicate signals from and to a base station controller or data router under the control of control processor 478. Signals received on antenna 460 are provided to analog receiver 462, where the signals are amplified, frequency translated and digitized in a  
25 process identical to that described in connection with the mobile station analog receiver. The output from the analog receiver 462 is provided to digital data receivers 466 and 468 and searcher receiver 464. The second receiver system (i.e., analog receiver 472, searcher receiver 474 and digital data receiver 476) processes the received signals in a manner similar to the  
30 first receiver system. The outputs of the digital data receivers 466, 476 are provided to diversity combiner and decoder circuitry 480, which processes the signals in accordance with a decoding algorithm. Details concerning the operation of the first and second receiver systems and the diversity combiner and decoder 980 are described in U.S. Patent No. 5,101,501 entitled  
35 "Method and Apparatus for Providing A Soft Handoff In Communications In A CDMA Cellular Telephone System", incorporated above. Signals for transmission to mobile units are provided to a transmit modulator 484 under the control of processor 478. Transmit modulator 484 modulates the data for transmission to the intended recipient mobile station.

Although the present invention has been described in connection with mobile radio communication systems that use CDMA modulation for transmitting signals between the mobile station and the base stations in the system, it will be understood by those skilled in the art that the teachings of  
5 the present invention could be applied in mobile radio communications that use other modulation methods such as, for example, time division multiple access modulation, for communicating between the mobile station and base stations in the system.

The previous description of the preferred embodiments is provided  
10 to enable any person skilled in the art to make or use the present invention. Various modifications to the embodiments described above will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without the use of inventive faculty. Thus, the present invention is not intended to be limited to the methods  
15 and apparatuses shown herein but is to be accorded the widest scope consistent with the claims set forth below.



## CLAIMS

1. In a mobile radio telephone system having a mobile station  
2 and at least one base station, wherein transmit power of a signal sent from  
the base station to the mobile station is controlled by a power control loop  
4 that attempts to maintain the transmit power of the signal above a first  
threshold, a method for dynamically adjusting the first threshold of the  
6 power control loop comprising the steps of:

8 (A) determining location information that is representative of a  
distance and a morphology between the mobile station and the  
base station;

10 (B) adjusting the first threshold of the power control loop in  
accordance with the location information; and

12 (C) repeating steps (A) - (B) while sending the signal from the base  
station to the mobile station at a power level that is controlled  
14 by the power control loop.

2. The method of claim 1, wherein the first threshold of the  
2 power control loop is adjusted in step (B) as the distance and the  
morphology between the mobile station and the base station change.

3. The method of claim 1, wherein step (A) further comprises  
2 determining velocity information that is representative of a velocity of the  
mobile station, and step (B) comprises adjusting the first threshold of the  
4 power control loop in accordance with the velocity information and the  
location information.

4. The method of claim 3, wherein the first threshold of the  
2 power control loop is adjusted downward in step (B) as the velocity of the  
mobile station decreases.

5. The method of claim 1, wherein the power control loop further  
2 attempts to maintain the transmit power of the signal below a second  
threshold, and step (B) further comprises adjusting the second threshold of  
4 the power control loop in accordance with the location information.

6. The method of claim 5, wherein step (A) further comprises  
2 determining velocity information that is representative of a velocity of the  
mobile station, and step (B) comprises adjusting the first and seconds  
4 thresholds of the power control loop in accordance with the velocity  
information and the location information.

7. The method of claim 1, wherein the power control loop adjusts  
2 the transmit power of the signal sent from the base station to the mobile  
station upward or downward in stepwise increments each of which has a  
4 step size, wherein step (A) further comprises determining velocity  
information that is representative of a velocity of the mobile station, and  
6 step (B) further comprises adjusting the step size of the power control loop  
in accordance with the velocity information.

8. The method of claim 1, wherein step (B) comprises the step of  
2 applying the location information to a table to determine the first threshold.

9. The method of claim 8, wherein a geographic cell having a  
2 plurality of different regions is serviced by the base station, and each of the  
regions has a different value for the first threshold.

10. In a mobile radio telephone system having a mobile station  
2 and at least one base station, wherein a signal to noise ratio (SNR) of a signal  
sent from the mobile station to the base station is controlled by a power  
4 control loop that attempts to maintain the SNR of the signal above a first  
threshold, a method for dynamically adjusting the first threshold of the  
6 power control loop comprising the steps of:

- 8 (A) determining location information that is representative of a  
distance and a morphology between the mobile station and the  
base station;
- 10 (B) adjusting the first threshold of the power control loop in  
accordance with the location information; and
- 12 (C) repeating steps (A) - (B) while sending the signal from the  
mobile station to the base station;
- 14 wherein the SNR of the signal is controlled by the power  
control loop during step (C).

11. The method of claim 10, wherein the first threshold of the power control loop corresponds to a minimum desired signal to noise ratio of the signal sent from the mobile station to the base station.

12. The method of claim 11, wherein the first threshold is adjusted in step (B) as the distance and the morphology between the mobile station and the base station change.

13. The method of claim 11, wherein step (A) further comprises determining velocity information that is representative of a velocity of the mobile station, and step (B) comprises adjusting the first threshold of the power control loop in accordance with the velocity information and the location information.

14. The method of claim 13, wherein the first threshold of the power control loop is adjusted downward in step (B) as the velocity of the mobile station decreases.

15. The method of claim 11, wherein the power control loop further attempts to maintain the SNR of the signal below a second threshold, and step (B) further comprises adjusting the second threshold of the power control loop in accordance with the location information.

16. The method of claim 15, wherein the second threshold of the power control loop corresponds to a maximum desired signal to noise ratio of the signal sent from the mobile station to the base station.

17. The method of claim 16, wherein step (A) further comprises determining velocity information that is representative of a velocity of the mobile station, and step (B) comprises adjusting the first and second thresholds of the power control loop in accordance with the velocity information and the location information.

18. The method of claim 11, wherein the power control loop adjusts the transmit power of the signal sent from the mobile station to the base station upward or downward in stepwise increments each of which has a step size, wherein step (A) further comprises determining velocity information that is representative of a velocity of the mobile station, and

- 6 step (B) further comprises adjusting the step size of the power control loop  
in accordance with the velocity information.

19. The method of claim 11, wherein step (B) comprises the step of  
2 applying the location information to a table to determine the first threshold.

20. The method of claim 19, wherein a geographic cell having a  
2 plurality of different regions is serviced by the base station, and each of the  
regions has a different value for the first threshold.

21. In a mobile radio telephone system having a mobile station  
2 and at least one base station, wherein transmit power of a signal sent from  
the base station to the mobile station is controlled by a power control loop  
4 that attempts to maintain the transmit power of the signal above a first  
threshold, a method for dynamically adjusting the first threshold of the  
6 power control loop comprising the steps of:

- 8 (A) determining velocity information that is representative of a  
velocity of the mobile station;  
10 (B) adjusting the first threshold of the power control loop in  
accordance with the velocity information; and  
12 (C) repeating steps (A) - (B) while sending the signal from the base  
station to the mobile station at a power level that is controlled  
by the power control loop.

22. The method of claim 21, wherein the first threshold of the  
2 power control loop is adjusted downward in step (B) as the speed of the  
mobile station decreases.

23. The method of claim 21, wherein the power control loop  
2 further attempts to maintain the transmit power of the signal below a  
second threshold, and step (B) further comprises adjusting the second  
4 threshold of the power control loop in accordance with the velocity  
information.

24. The method of claim 23, wherein the second threshold of the  
2 power control loop is adjusted upward in step (B) as the velocity of the  
mobile station decreases.

25. The method of claim 21, wherein the mobile radio telephone  
2 system includes mobile stations used by both fixed position wireless users  
and mobile wireless users.

26. In a mobile radio telephone system having a mobile station  
2 and at least one base station, wherein a signal to noise ratio (SNR) of a signal  
sent from the mobile station to the base station is controlled by a power  
4 control loop that attempts to maintain the SNR of the signal above a first  
threshold, a method for dynamically adjusting the first threshold of the  
6 power control loop comprising the steps of:

- 8 (A) determining velocity information that is representative of a  
velocity of the mobile station;
- 10 (B) adjusting the first threshold of the power control loop in  
accordance with the velocity information; and
- 12 (C) repeating steps (A) - (B) while sending the signal from the  
mobile station to the base station;

14 wherein the SNR of the signal is controlled by the power  
control loop during step (C).

27. The method of claim 26, wherein the first threshold of the  
2 power control loop corresponds to a minimum desired signal to noise ratio  
of the signal sent from the mobile station to the base station.

28. The method of claim 26, wherein the first threshold of the  
2 power control loop is adjusted downward in step (B) as the speed of the  
mobile station decreases.

29. The method of claim 26, wherein the power control loop  
2 further attempts to maintain the SNR of the signal below a second  
threshold, and step (B) further comprises adjusting the second threshold of  
4 the power control loop in accordance with the velocity information.

30. The method of claim 29, wherein the second threshold of the  
2 power control loop corresponds to a maximum desired signal to noise ratio  
of the signal sent from the mobile station to the base station.

31. The method of claim 30, wherein the second threshold of the  
2 power control loop is adjusted upward in step (B) as the speed of the mobile  
station decreases.

32. The method of claim 26, wherein the mobile radio telephone system includes mobile stations used by both fixed position wireless users and mobile wireless users.

33. In a mobile radio telephone system having a mobile station and at least one base station, wherein transmit power of a signal sent from the base station to the mobile station is controlled by a power control loop that adjusts the transmit power of the signal upward or downward in stepwise increments each of which has a step size, a method for dynamically adjusting the step size of the power control loop comprising the steps of:

- (A) determining velocity information that is representative of a velocity of the mobile station;
- (B) adjusting the step size of the power control loop in accordance with the velocity information; and
- (C) repeating steps (A) - (B) while sending the signal from the base station to the mobile station at a power level that is controlled by the power control loop.

34. In a mobile radio telephone system having a mobile station and at least one base station, wherein a signal to noise ratio (SNR) of a signal sent from the mobile station to the base station is controlled by a power control loop that adjusts the transmit power of the signal upward or downward in stepwise increments each of which has a step size, a method for dynamically adjusting the step size of the power control loop comprising the steps of:

- (A) determining velocity information that is representative of a velocity of the mobile station;
- (B) adjusting the step size of the power control loop in accordance with the velocity information; and
- (C) repeating steps (A) - (B) while sending the signal from the mobile station to the base station;

wherein the SNR of the signal is controlled by the power control loop during step (C).

35. In a mobile radio telephone system having a mobile station and at least one base station, wherein transmit power of a signal sent from the base station to the mobile station is controlled by a power control loop that attempts to maintain the transmit power of the signal above a first

threshold, an apparatus for dynamically adjusting the first threshold of the  
6 power control loop, comprising:

- 8 (A) a controller that determines location information that is  
representative of a distance and a morphology between the  
10 mobile station and the base station, and adjusts the first  
threshold of the power control loop in accordance with the  
location information; and
- 12 (B) a transmitter, responsive to the power control loop, that  
transmits the signal from the base station to the mobile station.

36. In a mobile radio telephone communication system having a  
2 mobile station and at least one base station, wherein transmit power of a  
signal sent from the base station to the mobile station is controlled by a  
4 power control loop that attempts to maintain the transmit power of the  
signal above a first threshold, an apparatus for dynamically adjusting the  
6 first threshold of the power loop, comprising:

- 8 (A) means for determining location information that is  
representative of a distance and a morphology between the  
mobile station and the base station;
- 10 (B) means for adjusting the first threshold of the power control  
loop in accordance with the location information; and
- 12 (C) means, responsive to the power control loop, for transmitting  
the signal from the base station to the mobile station.

2

37. In a mobile radio telephone system having a mobile station  
2 and at least one base station, wherein a signal to noise ratio (SNR) of a signal  
sent from the mobile station to the base station is controlled by a power  
4 control loop that attempts to maintain the SNR of the signal above a first  
threshold, an apparatus for dynamically adjusting the first threshold of the  
6 power control loop, comprising:

- 8 (A) a controller that determines location information that is  
representative of a distance and a morphology between the  
mobile station and the base station, and adjusts the first  
10 threshold of the power control loop in accordance with the  
location information; and
- 12 (B) a transmitter, responsive to the power control loop, that  
transmits the signal from the mobile station to the base station.

2 38. In a mobile radio telephone communication system having a  
mobile station and at least one base station, wherein a signal to noise ratio  
(SNR) of a signal sent from the mobile station to the base station is  
4 controlled by a power control loop that attempts to maintain the SNR of the  
signal above a first threshold, an apparatus for dynamically adjusting the  
6 first threshold of the power loop, comprising:

- 8 (A) means for determining location information that is  
representative of a distance and a morphology between the  
mobile station and the base station;
- 10 (B) means for adjusting the first threshold of the power control  
loop in accordance with the location information; and
- 12 (C) means, responsive to the power control loop, for transmitting  
the signal from the mobile station to the base station.

2 39. In a mobile radio telephone system having a mobile station  
2 and at least one base station, wherein transmit power of a signal sent from  
the base station to the mobile station is controlled by a power control loop  
4 that attempts to maintain the transmit power of the signal above a first  
threshold, an apparatus for dynamically adjusting the first threshold of the  
6 power control loop, comprising:

- 8 (A) a controller that determines velocity information that is  
representative of a velocity of the mobile station, and adjusts  
the first threshold of the power control loop in accordance with  
10 the velocity information; and
- 12 (B) a transmitter, responsive to the power control loop, that  
transmits the signal from the base station to the mobile station.

2 40. In a mobile radio telephone communication system having a  
mobile station and at least one base station, wherein transmit power of a  
signal sent from the base station to the mobile station is controlled by a  
4 power control loop that attempts to maintain the transmit power of the  
signal above a first threshold, an apparatus for dynamically adjusting the  
6 first threshold of the power loop, comprising:

- 8 (A) means for determining velocity information that is  
representative of a velocity of the mobile station;
- 10 (B) means for adjusting the first threshold of the power control  
loop in accordance with the velocity information; and



12 (C) means, responsive to the power control loop, for transmitting  
the signal from the base station to the mobile station.

2

2 41. In a mobile radio telephone system having a mobile station  
and at least one base station, wherein a signal to noise ratio (SNR) of a signal  
4 sent from the mobile station to the base station is controlled by a power  
control loop that attempts to maintain the SNR of the signal above a first  
6 threshold, an apparatus for dynamically adjusting the first threshold of the  
power control loop, comprising:

8 (A) a controller that determines velocity information that is  
representative of a velocity of the mobile station, and adjusts  
10 the first threshold of the power control loop in accordance with  
the velocity information; and

12 (B) a transmitter, responsive to the power control loop, that  
transmits the signal from the mobile station to the base station.

2 42. In a mobile radio telephone communication system having a  
mobile station and at least one base station, wherein a signal to noise ratio  
(SNR) of a signal sent from the mobile station to the base station is  
4 controlled by a power control loop that attempts to maintain the SNR of the  
signal above a first threshold, an apparatus for dynamically adjusting the  
6 first threshold of the power loop, comprising:

8 (A) means for determining velocity information that is  
representative of a velocity of the mobile station;

10 (B) means for adjusting the first threshold of the power control  
loop in accordance with the velocity information; and

12 (C) means, responsive to the power control loop, for transmitting  
the signal from the mobile station to the base station.

2

2 43. In a mobile radio telephone system having a mobile station  
and at least one base station, wherein transmit power of a signal sent from  
the base station to the mobile station is controlled by a power control loop  
4 that adjusts the transmit power of the signal upward or downward in  
stepwise increments each of which has a step size, an apparatus for  
6 dynamically adjusting the step size of the power control loop, comprising:

8 (A) a controller that determines velocity information that is  
representative of a velocity of the mobile station, and adjusts

- 10 the step size of the power control loop in accordance with the  
velocity information; and  
12 (B) a transmitter, responsive to the power control loop, that  
transmits the signal from the base station to the mobile station.

44. In a mobile radio telephone communication system having a  
2 mobile station and at least one base station, wherein transmit power of a  
signal sent from the base station to the mobile station is controlled by a  
4 power control loop that adjusts the transmit power of the signal upward or  
downward in stepwise increments each of which has a step size, an  
6 apparatus method for dynamically adjusting the step size of the power  
control loop, comprising:  
8 (A) means for determining velocity information that is  
representative of a velocity of the mobile station;  
10 (B) means for adjusting the step size of the power control loop in  
accordance with the velocity information; and  
12 (C) means, responsive to the power control loop, for transmitting  
the signal from the base station to the mobile station.

- 2  
45. In a mobile radio telephone system having a mobile station  
2 and at least one base station, wherein a signal to noise ratio (SNR) of a signal  
sent from the mobile station to the base station is controlled by a power  
4 control loop that adjusts the transmit power of the signal upward or  
downward in stepwise increments each of which has a step size, an  
6 apparatus for dynamically adjusting the step size of the power control loop,  
comprising:  
8 (A) a controller that determines velocity information that is  
representative of a velocity of the mobile station, and adjusts  
10 the step size of the power control loop in accordance with the  
velocity information; and  
12 (B) a transmitter, responsive to the power control loop, that  
transmits the signal from the mobile station to the base station.

46. In a mobile radio telephone communication system having a  
2 mobile station and at least one base station, wherein a signal to noise ratio  
(SNR) of a signal sent from the mobile station to the base station is  
4 controlled by a power control loop that adjusts the transmit power of the  
signal upward or downward in stepwise increments each of which has a step

- 6 size, an apparatus for dynamically adjusting the step size of the power  
control loop, comprising:
- 8 (A) means for determining velocity information that is  
representative of a velocity of the mobile station;
- 10 (B) means for adjusting the step size of the power control loop in  
accordance with the velocity information; and
- 12 (C) means, responsive to the power control loop, for transmitting  
the signal from the mobile station to the base station.





FIG. 1



MORPHOLOGIC REGIONS WITHIN CELL COVERAGE

FIG. 2

3/4




FIG. 3




FIG. 4

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/28394

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H0487/005

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 H048

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
X A	<p>WO 96 31014 A (QUALCOMM INC) 3 October 1996 (1996-10-03)</p> <p>page 6, line 13 -page 9, line 8 page 11, line 35 -page 12, line 16 page 12, line 22 - line 26 figures 2A, 2B</p> <p style="text-align: center;">-/--</p>	<p>1-7, 21-24, 33-46, 10-18, 26-29, 31</p>

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"S" document member of the same patent family

Date of the actual completion of the international search

30 March 2000

Date of mailing of the international search report

07/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Gkeli, M



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/28394

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 778 030 A (BRUCKERT EUGENE J ET AL) 7 July 1998 (1998-07-07)	26, 34
A	column 2, line 30 - line 67	21, 33
A	column 3, line 38 - line 48	39-46
	column 4, line 49 - column 5, line 63	
	column 8, line 1 - line 30	
	column 11, line 42 - column 12, line 63	
	claims 1, 2, 4, 5, 7, 8, 10, 11, 14	
	figures 2-5	
	---	
A	US 5 465 399 A (NITARDY JOHN H ET AL) 7 November 1995 (1995-11-07)	1, 10, 21, 26, 33-46
	abstract	
	column 9, line 44 - column 10, line 17	
	column 2, line 40 - column 4, line 4	
	column 5, line 21 - column 6, line 36	
	column 7, line 4 - line 57	
	claim 1	
	---	
A	WO 96 03813 A (QUALCOMM INC) 8 February 1996 (1996-02-08)	1, 10, 21, 26, 33-46
	page 5, line 26 - page 6, line 2	
	claims 1, 2, 4-9	
	figure 1	
	-----	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/28394

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9631014 A	03-10-1996	AU 710025 B	09-09-1999
		AU 5378296 A	16-10-1996
		BR 9607976 A	13-01-1998
		CA 2216729 A	03-10-1996
		EP 0818084 A	14-01-1998
		JP 11502991 T	09-03-1999
		US 6035209 A	07-03-2000
		ZA 9602030 A	16-07-1996
US 5778030 A	07-07-1998	BR 9702091 A	20-07-1999
		CA 2219997 A	18-09-1997
		CN 1182508 A	20-05-1998
		EP 0826273 A	04-03-1998
		JP 11506899 T	15-06-1999
		WO 9734372 A	18-09-1997
		NONE	
US 5465399 A	07-11-1995		
WO 9603813 A	08-02-1996	US 5604730 A	18-02-1997
		AU 701510 B	28-01-1999
		AU 3003195 A	22-02-1996
		BR 9508428 A	23-12-1997
		CA 2195984 A	08-02-1996
		EP 0774179 A	21-05-1997
		FI 970319 A	13-03-1997
		IL 114703 A	06-12-1998
		JP 10503337 T	24-03-1998
		ZA 9505843 A	15-03-1996